

# L<sup>A</sup>T<sub>E</sub>X: 2D Graphs

DR. YIHSIANG LIOW (APRIL 4, 2023)


## Contents

<b>1</b>	<b>The <i>xy</i>-plane</b> ( <code>xy-plane.tex</code> )	<b>2</b>
<b>2</b>	<b>The <i>xy</i>-plane: text</b>	<b>5</b>
<b>3</b>	<b>minipage</b>	<b>11</b>
<b>4</b>	<b>Nested tikzpicture</b>	<b>17</b>
<b>5</b>	<b>Circles and Dots</b>	<b>18</b>
<b>6</b>	<b>Rectangle</b>	<b>22</b>
<b>7</b>	<b>Line</b>	<b>26</b>
<b>8</b>	<b>The <i>xy</i>-plane: Polar Coordinates</b> ( <code>xy-plane-polar-coord.tex</code> )	<b>28</b>
<b>9</b>	<b>Variable Points and Operations</b> ( <code>variable.tex</code> )	<b>29</b>
<b>10</b>	<b>PgfPlots</b> ( <code>pgfplots.tex</code> )	<b>31</b>
<b>11</b>	<b>pgfplots: Default Window</b> ( <code>xy-plane-default-window.tex</code> )	<b>32</b>
<b>12</b>	<b>pgfplots: Width and Height</b> ( <code>pgfplots-width-height.tex</code> )	<b>33</b>
<b>13</b>	<b>pgfplots: Label Axes</b> ( <code>pgfplots-label-axis.tex</code> )	<b>34</b>
<b>14</b>	<b>pgfplots: Grid</b> ( <code>pgfplots-2d-grid.tex</code> )	<b>35</b>
<b>15</b>	<b>pgfplots: Line Plots</b> ( <code>pgfplots-line.tex</code> )	<b>36</b>
<b>16</b>	<b>pgfplots: Color</b> ( <code>pgfplots-2d-color.tex</code> )	<b>38</b>
<b>17</b>	<b>pgfplots: Marker styles</b> ( <code>pgfplots-marker.tex</code> )	<b>39</b>
<b>18</b>	<b>pgfplots: Dashed Styles</b> ( <code>pgfplots-dashed.tex</code> )	<b>43</b>


<b>19 pgfplots: Dotted Styles</b> ( <code>pgfplots-dotted.tex</code> )	<b>45</b>
<b>20 pgfplots: Functions</b> ( <code>pgfplots-2d-function.tex</code> )	<b>47</b>
<b>21 pgfplots: Domain for all Functions</b> ( <code>xy-plane-domain-all.tex</code> )	<b>48</b>
<b>22 pgfplots: Domain for each Function</b> ( <code>xy-plane-domain-each-function.tex</code> )	<b>49</b>
<b>23 pgfplots: Sample Size</b> ( <code>pgfplots-sample-size.tex</code> )	<b>50</b>
<b>24 pgfplots: Legend</b> ( <code>xy-plane-legend.tex</code> )	<b>52</b>
<b>25 pgfplots: Max and min for axes</b> ( <code>xy-plane-axes-max-min.tex</code> )	<b>53</b>
<b>26 pgfplots: Place Axes in Middle</b> ( <code>xy-plane-place-axes.tex</code> )	<b>54</b>
<b>27 pgfplots: Points</b> ( <code>pgfplots-points.tex</code> )	<b>55</b>
<b>28 pgfplots: Insert PGF node</b> ( <code>pgfplots-insert-node.tex</code> )	<b>57</b>
<b>29 pgfplots: Node with pin</b> ( <code>pgfplots-pin.tex</code> )	<b>58</b>
<b>30 pgfplots: Pin Direction</b> ( <code>pgfplots-pin-direction.tex</code> )	<b>60</b>
<b>31 pgfplots: Shade Area</b> ( <code>xy-plane-area.tex</code> )	<b>61</b>
<b>32 pgfplots: Steps</b> ( <code>xy-plane-step.tex</code> )	<b>64</b>

# 1 The $xy$ -plane (xy-plane.tex)


Here's the  $xy$ -plane:




You can change the arrow tip:




This one only has the first quadrant:



After drawing your diagram if you find it too cramped up, you don't have to rescale by hand. You just do this:



Let me add values on the  $x$ -axis:



### L<sup>A</sup>T<sub>E</sub>X code

Here's the  $xy$ -plane:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-3,-3) grid (3,3);
\draw[->] (-3,0) -- (3,0);
\draw[->] (0,-3) -- (0,3);
\end{tikzpicture}
\end{center}
```

You can change the arrow tip:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-3,-3) grid (3,3);
\draw[->, >=triangle 60] (-3,0) -- (3,0);
\draw[->, >=triangle 60] (0,-3) -- (0,3);
\end{tikzpicture}
\end{center}
```

```
\end{tikzpicture}
\end{center}
```

This one only has the first quadrant:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (0,0) grid (3,3);
\draw[->] (0,0) -- (3,0);
\draw[->] (0,0) -- (0,3);
\end{tikzpicture}
\end{center}
```

After drawing your diagram if you find it too cramped up, you don't have to rescale by hand.

You just do this:

```
\begin{center}
\begin{tikzpicture}[scale=2]
\draw[step=1cm,gray,very thin] (0,0) grid (3,3);
\draw[->] (0,0) -- (3,0);
\draw[->] (0,0) -- (0,3);
\end{tikzpicture}
\end{center}
```

Let me add values on the  $x$ -axis:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) -- (3,0);
\draw[->] (0,-1) -- (0,3);


\draw (-0.2,-0.2) node {0};
\draw (1,-0.2) node {1};
\draw (2,-0.2) node {2};
\draw (3.2,0) node {$x$};
\end{tikzpicture}
\end{center}
```

## 2 The $xy$ -plane: text

You can put a text box at (1,1):

```
\draw (1,1) node[] {helloworld ... lorem ipsum};


\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0);
\draw[->] (0,-1) -- (0,3);
```



You can give text a background color:


```
\draw (1,1) node[fill=yellow] {helloworld ... lorem ipsum};

\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```




You can change the font size:

```
\draw (1,1) node[fill=yellow, font=\tiny] {helloworld ... lorem ipsum};
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



You can vary the inner sep (the border spacing):


```
\draw (1,1) node[fill=yellow, inner sep=1cm] {helloworld ... lorem ipsum};
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



You can have rounded corners:

```
\draw (1,1) node[fill=yellow, inner sep=1cm, rounded corners]
    {helloworld ... lorem ipsum};


\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



You can specify the radius of the rounded corners:

```
\draw (1,1) node[fill=yellow, inner sep=1cm, rounded corners=0.5cm]
    {helloworld ... lorem ipsum};


\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



You can draw the boundary:

```
\draw (1,1) node[draw, fill=yellow, inner sep=1cm, rounded corners=0.5cm]
    {helloworld ... lorem ipsum};


\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



You can specify the line width:

```
\draw (1,1) node[draw, fill=yellow, inner sep=1cm, rounded corners=0.5cm,
    line width=0.1cm]
    {helloworld ... lorem ipsum};


\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



You can specify the line style:


```
\draw (1,1) node[draw, fill=yellow, inner sep=1cm, rounded corners=0.5cm,  
                line width=0.1cm, dashed]  
                {helloworld ... lorem ipsum};
```

```
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);  
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



If you specify the foreground color something goes wrong (see the section on minipage on how to fix this problem):

```
\draw (1,1) node[draw, fill=yellow, inner sep=1cm, rounded corners=0.5cm,  
                line width=0.1cm, dashed, color=red]  
                {helloworld ... lorem ipsum};  
  
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);  
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```




### 3 minipage

You can put a minipage at a node. You can specify the width and height of the minipage.

If you leave out the height:


```
\draw (1,1) node[fill=yellow] {  
  \begin{minipage}[t] [] {3cm}  
    helloworld ... lorem ipsum  
  \end{minipage}  
};  
  
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);  
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



And use rounded corners and a minipage:

```
\draw (1,1) node[fill=yellow, rounded corners] {
  \begin{minipage}[t][2cm]{3cm}
    helloworld ... lorem ipsum
  \end{minipage}
};


\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



Rounded corners with specified radius:


```
\draw (1,1) node[fill=yellow, rounded corners=0.5cm] {
  \begin{minipage}[t][2cm]{3cm}
    helloworld ... lorem ipsum
  \end{minipage}
};

\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



It looks better in this case to increase the inner sep (say inner sep = radius):


```
\draw (1,1) node[fill=yellow, rounded corners=0.5cm, inner sep=0.5cm] {  
  \begin{minipage}[t][2cm]{3cm}  
    helloworld ... lorem ipsum  
  \end{minipage}  
};  
  
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);  
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



You can draw the boundary:

```
\draw (1,1) node[draw, fill=yellow, rounded corners] {
  \begin{minipage}[t][2cm]{3cm}
    helloworld ... lorem ipsum
  \end{minipage}
};


\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



You can choose the line width for the boundary:

```
\draw (1,1) node[draw, fill=yellow, rounded corners, line width=0.1cm] {
  \begin{minipage}[t][2cm]{3cm}
    helloworld ... lorem ipsum
  \end{minipage}
};


\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



You can choose the the line style for the boundary:

```
\draw (1,1) node[draw, fill=yellow, rounded corners, line width=0.1cm,
                 dashed] {
  \begin{minipage}[t][2cm]{3cm}
    helloworld ... lorem ipsum
  \end{minipage}
};


\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```



You can choose foreground color:

```
\draw (1,1) node[draw, color=red, fill=yellow, line width=0.1cm,
                 rounded corners] {
  \begin{minipage}[t][2cm]{3cm}
    helloworld ... lorem ipsum
  \end{minipage}
};

\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);
```




Center-justify the contents of the node:

```

\draw (1,1) node[draw, color=red, fill=yellow, line width=0.1cm,
                 rounded corners] {
  \begin{minipage}[c] [2cm]{3cm}
    helloworld ... lorem ipsum
  \end{minipage}
};

\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);

```




Bottom-justify the contents of the node:

```

\draw (1,1) node[draw, color=red, fill=yellow, line width=0.1cm,
                 rounded corners] {
  \begin{minipage}[b] [2cm]{3cm}
    helloworld ... lorem ipsum
  \end{minipage}
};

\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0); \draw[->] (0,-1) -- (0,3);

```



Note that the extra border (due to the inner sep) is beyond the specified width and height.

## 4 Nested tikzpicture


Nested tikzpicture works:

```

\begin{tikzpicture}
\draw (1,1) node[draw, color=red, fill=yellow, line width=2,
                style=rounded corners] {%
  \begin{minipage}[b][2cm]{2cm}
  \begin{tikzpicture}
  \draw[step=0.5cm,gray,very thin] (-1,-1) grid (1,1);
  \draw[->, line width=0.1cm] (0,0) -- (1,0);
  \end{tikzpicture}
  \end{minipage}
};

\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) --(3,0);
\draw[->] (0,-1) -- (0,3);
\end{tikzpicture}

```




## 5 Circles and Dots

Here's a circle at (1,1) of radius 0.5:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) -- (3,0);
\draw[->] (0,-1) -- (0,3);


\draw (1,1) circle (0.5cm);
\end{tikzpicture}
\end{center}
```



I can fill it:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) -- (3,0);
\draw[->] (0,-1) -- (0,3);


\filldraw (1,1) circle (0.5cm);
\end{tikzpicture}
\end{center}
```



I can fill with different colors:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) -- (3,0);
\draw[->] (0,-1) -- (0,3);


\filldraw[fill=red] (1,1) circle (0.5cm);
\end{tikzpicture}
\end{center}
```



I can also shade it:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) -- (3,0);
\draw[->] (0,-1) -- (0,3);


\shade[ball color=red] (1,1) circle (0.5cm);
\end{tikzpicture}
\end{center}
```



OK ... I don't think you need shaded balls on a *flat* 2-d plane. However you probably want to draw point which are just small circles:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) -- (3,0);
\draw[->] (0,-1) -- (0,3);

\filldraw (1,1) circle (0.05cm);
\filldraw (1.5,2.7) circle (0.05cm);
\end{tikzpicture}
\end{center}
```




And you might want to label their coordinates:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-1,-1) grid (3,3);
\draw[->] (-1,0) -- (3,0);
\draw[->] (0,-1) -- (0,3);

\filldraw (1,1) circle (0.05cm);
\draw (1,0.5) node {$(1,1)$};

\filldraw (1.5,2.7) circle (0.05cm);
\draw (1.5,2.2) node {$(1.5,2.2)$};


\end{tikzpicture}
\end{center}
```



## 6 Rectangle

```
\draw (1,1) rectangle (3, 2);


\draw[step=1cm,gray,very thin] (-1,-1) grid (4,3);
\draw[->] (-1,0) --(4,0); \draw[->] (0,-1) -- (0,3);
```



You can choose a line width:

```
\draw[line width=0.2cm] (1,1) rectangle (3, 2);


\draw[step=1cm,gray,very thin] (-1,-1) grid (4,3);
\draw[->] (-1,0) --(4,0); \draw[->] (0,-1) -- (0,3);
```



You can choose a color:

```
\draw[line width=0.2cm, color=red!60!white] (1,1) rectangle (3, 2);


\draw[step=1cm,gray,very thin] (-1,-1) grid (4,3);
\draw[->] (-1,0) --(4,0); \draw[->] (0,-1) -- (0,3);
```



Rounded corners:

```
\draw[line width=0.2cm, color=red!60!white, rounded corners=0.25cm]
  (1,1) rectangle (3, 2);


\draw[step=1cm,gray,very thin,radius=0.5cm] (-1,-1) grid (4,3);
\draw[->] (-1,0) --(4,0); \draw[->] (0,-1) -- (0,3);
```



Dashed line style:

```
\draw[line width=0.2cm, color=red!60!white, rounded corners=0.25cm,
  dashed]
  (1,1) rectangle (3, 2);


\draw[step=1cm,gray,very thin,radius=0.5cm] (-1,-1) grid (4,3);
\draw[->] (-1,0) --(4,0); \draw[->] (0,-1) -- (0,3);
```



Double line style:

```
\draw[line width=0.2cm, color=red!60!white, rounded corners=0.25cm,
double]
(1,1) rectangle (3, 2);


\draw[step=1cm,gray,very thin,radius=0.5cm] (-1,-1) grid (4,3);
\draw[->] (-1,0) --(4,0); \draw[->] (0,-1) -- (0,3);
```



You can color the interior:

```
\filldraw[line width=0.2cm, color=red!60!white, rounded corners=0.25cm]
(1,1) rectangle (3, 2);

\draw[fill=yellow,step=1cm,gray,very thin,radius=0.5cm] (-1,-1) grid (4,3);
\draw[->] (-1,0) --(4,0); \draw[->] (0,-1) -- (0,3);
```




## 7 Line

Here's a line:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-1,-1) grid (6,4);
\draw[->] (-1,0) -- (6,0);
\draw[->] (0,-1) -- (0,4);


\draw[very thick] (1,1) -- (5.5,3.5);
\end{tikzpicture}
\end{center}
```



I can change the thickness and the color:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-1,-1) grid (6,4);
\draw[->] (-1,0) -- (6,0);
\draw[->] (0,-1) -- (0,4);

\draw[red, line width=0.25cm] (1,1) -- (5.5,3.5);
\end{tikzpicture}
\end{center}
```



Here's Pythagorus' theorem in action (I removed the grid):

```

\begin{center}
\begin{tikzpicture}
\draw[->] (-1,0) -- (10,0);
\draw[->] (0,-1) -- (0,4);


\draw[very thick] (3,1) -- (8.5,3.5);
\draw[very thick] (8.5,1) -- (8.5,3.5);
\draw[very thick] (3,1) -- (8.5,1);

\filldraw (3,1) circle (0.07);
\filldraw (8.5,3.5) circle (0.07);

\draw (3,0.5) node {$(x_0, y_0)$};
\draw (9.5,3.5) node {$(x_1, y_1)$};
\draw (3,2.5) node {$\sqrt{(x_1 - x_0)^2 + (y_1 - y_0)^2}$};


\end{tikzpicture}
\end{center}

```



## 8 The $xy$ -plane: Polar Coordinates (xy-plane-polar-coord.tex)

You can specify points in polar coordinates in the form (angle:radius). WARNING: The angle is in degrees, not radians.



### L<sup>A</sup>T<sub>E</sub>X code


You can specify points in polar coordinates in the form (angle:radius). WARNING: The angle is in degrees, not radians.

```
\begin{center}
\begin{tikzpicture}
\draw (0:1) -- (60:1) -- (120:1)
      -- (180:1) -- (240:1) -- (300:1) -- (360:1)
;
\end{tikzpicture}
\end{center}
```


## 9 Variable Points and Operations (variable.tex)

You can create variables for points and do simple operations on them.

The following hardcoded points:



The following is the same but uses variables and operations:



### L<sup>A</sup>T<sub>E</sub>X code

You can create variables for points and do simple operations on them.

The following hardcoded points:

```
\begin{center}
\begin{tikzpicture}
\draw[step=1cm,gray,very thin] (-1,-1) grid (6,4);
\draw[->] (-1,0) -- (6,0);
\draw[->] (0,-1) -- (0,4);
```

```
\draw[very thick] (1,1) -- (5.5,3.5);  
\end{tikzpicture}  
\end{center}
```

The following is the same but uses variables and operations:

```
\begin{center}  
\begin{tikzpicture}  
\draw[step=1cm,gray,very thin] (-1,-1) grid (6,4);  
\draw[->] (-1,0) -- (6,0);  
\draw[->] (0,-1) -- (0,4);  
  
\path (1,1) coordinate (A);  
\path (A) ++(4.5, 2.5) coordinate (B);  
  
\draw[very thick] (A) -- (B);  
\end{tikzpicture}  
\end{center}
```

## 10 PgfPlots (pgfplots.tex)

The following sections use the pgfplots library for 2D diagrams. The pgfplots library is built on top of the pgf/tikz library. It makes drawing 2D plots easier.


Pgfplots can also draw 3D plots.

### L<sup>A</sup>T<sub>E</sub>X code

The following sections use the pgfplots library for 2D diagrams.  
The pgfplots library is built on top of the pgf/tikz library.  
It makes drawing 2D plots easier.

Pgfplots can also draw 3D plots.


## 11 pgfplots: Default Window (xy-plane-default-window.tex)



### L<sup>A</sup>T<sub>E</sub>X code

```
\begin{center}  
\begin{tikzpicture}  
\begin{axis}  
\end{axis}  
\end{tikzpicture}  
\end{center}
```


## 12 pgfplots: Width and Height (pgfplots-width-height.tex)



### L<sup>A</sup>T<sub>E</sub>X code

```
\begin{center}
\begin{tikzpicture}
\begin{axis}[width=6in, height=2in]
\end{axis}
\end{tikzpicture}
\end{center}
```


## 13 pgfplots: Label Axes (pgfplots-label-axis.tex)



### L<sup>A</sup>T<sub>E</sub>X code

```
\begin{center}
\begin{tikzpicture}
\begin{axis}[
xlabel=Cost,
ylabel=Error]
\end{axis}
\end{tikzpicture}
\end{center}
```



## 14 pgfplots: Grid (pgfplots-2d-grid.tex)



### L<sup>A</sup>T<sub>E</sub>X code

```
\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}[grid=major]
\end{axis}
\end{tikzpicture}
\end{center}
```

## 15 pgfplots: Line Plots (pgfplots-line.tex)




### L<sup>A</sup>T<sub>E</sub>X code

```
\begin{center}
\begin{tikzpicture}
\begin{axis}
\addplot coordinates {(0,0.5) (1,2) (2,1.5)};
\end{axis}
\end{tikzpicture}
\end{center}

\begin{center}
\begin{tikzpicture}
\begin{axis}
```

```
\addplot coordinates {(0,0.5) (1,2) (2,1.5)};  
\addplot coordinates {(0,1) (1.5,0.5) (2,0)};  
\end{axis}  
\end{tikzpicture}  
\end{center}
```

## 16 pgfplots: Color (pgfplots-2d-color.tex)



Note: If you specify a style [...], then the default style is removed.


### L<sup>A</sup>T<sub>E</sub>X code

```
\begin{center}
\begin{tikzpicture}
\begin{axis}
\addplot [black] coordinates {(0,0.5) (1,2) (2,1.5)};
\addplot [red] coordinates {(0,1) (1.5,0.5) (2,0)};
\end{axis}
\end{tikzpicture}
\end{center}
```


Note: If you specify a style `\verb![...]`!, then the default style is removed.

## 17 pgfplots: Marker styles (pgfplots-marker.tex)


No marker:




Filled dot marker (default, color default):




x Marker:




o Marker:




Triangle Marker:




Filled Triangle Marker:



Square Marker:



Filled Square Marker:



### L<sup>A</sup>T<sub>E</sub>X code

```
No marker:  
\begin{center}  
\begin{tikzpicture}  
\begin{axis}[height=2in]  
\addplot[no markers] coordinates {(0,0) (1,2) (2,1)};  
\end{axis}  
\end{tikzpicture}  
\end{center}  
  
Filled dot marker (default, color default):  
\begin{center}  
\begin{tikzpicture}  
\begin{axis}[height=2in]  
\addplot+[sharp plot] coordinates {(0,0) (1,2) (2,1)};  
\end{axis}  
\end{tikzpicture}  
\end{center}  
  
x Marker:  
\begin{center}  
\begin{tikzpicture}  
\begin{axis}[height=2in]  
\addplot[mark=x] coordinates {(0,0) (1,2) (2,1)};  
\end{axis}  
\end{tikzpicture}  
\end{center}  
  
o Marker:  
\begin{center}  
\begin{tikzpicture}
```

```
\begin{axis}[height=2in]
\addplot[mark=o] coordinates {(0,0) (1,2) (2,1)};
\end{axis}
\end{tikzpicture}
\end{center}
```

Triangle Marker:

```
\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in]
\addplot[mark=triangle] coordinates {(0,0) (1,2) (2,1)};
\end{axis}
\end{tikzpicture}
\end{center}
```

Filled Triangle Marker:

```
\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in]
\addplot[mark=triangle*] coordinates {(0,0) (1,2) (2,1)};
\end{axis}
\end{tikzpicture}
\end{center}
```

Square Marker:


```
\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in]
\addplot[mark=square] coordinates {(0,0) (1,2) (2,1)};
\end{axis}
\end{tikzpicture}
\end{center}
```

Filled Square Marker:


```
\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in]
\addplot[mark=square*] coordinates {(0,0) (1,2) (2,1)};
\end{axis}
\end{tikzpicture}
\end{center}
```

## 18 pgfplots: Dashed Styles (pgfplots-dashed.tex)


Dashed:



Densely dashed:



Loosely dashed:



### L<sup>A</sup>T<sub>E</sub>X code

```
Dashed:  
  
\begin{center}  
\begin{tikzpicture}  
\begin{axis}[height=2in]
```

```
\addplot[sharp plot, dashed] coordinates
{(0,0.5) (1,2) (2,1.5)};
\end{axis}
\end{tikzpicture}
\end{center}
```

Densely dashed:


```
\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in]
\addplot[sharp plot, densely dashed] coordinates
{(0,0.5) (1,2) (2,1.5)};
\end{axis}
\end{tikzpicture}
\end{center}
```

Loosely dashed:


```
\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in]
\addplot[sharp plot, loosely dashed] coordinates
{(0,0.5) (1,2) (2,1.5)};
\end{axis}
\end{tikzpicture}
\end{center}
```

## 19 pgfplots: Dotted Styles (pgfplots-dotted.tex)


Dotted:



Loosely dotted:



Densely dotted:



### L<sup>A</sup>T<sub>E</sub>X code

```
Dotted:  
  
\begin{center}  
\begin{tikzpicture}  
\begin{axis}[height=2in]
```

```
\addplot[sharp plot, dotted] coordinates
{(0,0.5) (1,2) (2,1.5)};
\end{axis}
\end{tikzpicture}
\end{center}
```

Loosely dotted:


```
\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in]
\addplot[sharp plot, loosely dotted] coordinates
{(0,0.5) (1,2) (2,1.5)};
\end{axis}
\end{tikzpicture}
\end{center}
```

Densely dotted:

```
\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in]
\addplot[sharp plot, densely dotted] coordinates
{(0,0.5) (1,2) (2,1.5)};
\end{axis}
\end{tikzpicture}
\end{center}
```

## 20 pgfplots: Functions (pgfplots-2d-function.tex)

[WARNING: angles are in degrees, not radians.]




### L<sup>A</sup>T<sub>E</sub>X code

```
[WARNING: angles are in degrees, not radians.]

\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}
\addplot[draw=red, ultra thick] {sin(180*x/3.14)};
\addplot[draw=blue, line width=1] {x};
\end{axis}
\end{tikzpicture}
\end{center}
```


## 21 pgfplots: Domain for all Functions (xy-plane-domain-all.tex)



### L<sup>A</sup>T<sub>E</sub>X code

```
\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}[domain=0:10]
\addplot[draw=red, ultra thick] {sin(180*x/3.14)};
\addplot[draw=blue, line width=1] {x};
\end{axis}
\end{tikzpicture}
\end{center}
```

## 22 pgfplots: Domain for each Function (xy-plane-domain-each-function.tex)




### L<sup>A</sup>T<sub>E</sub>X code


```
\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}
\addplot[draw=red, domain=0:10, ultra thick] {sin(180*x/3.14)};
\addplot[draw=blue, domain=3:5, line width=1] {x};
\end{axis}
\end{tikzpicture}
\end{center}
```

## 23 pgfplots: Sample Size (pgfplots-sample-size.tex)

Default sample size:



Sample size = 1000:



### L<sup>A</sup>T<sub>E</sub>X code

Default sample size:


```
\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}[domain=0:1000]
\addplot[draw=red, line width=1] {x * sin(x)};
\end{axis}
\end{tikzpicture}
\end{center}
```

```
\end{tikzpicture}  
\end{center}
```

Sample size = 1000:

```
\begin{center}  
\begin{tikzpicture}[line width=2]  
\begin{axis}[domain=0:1000]  
\addplot[draw=red, line width=1, samples=1000] {x * sin(x)};  
\end{axis}  
\end{tikzpicture}  
\end{center}
```


## 24 pgfplots: Legend (xy-plane-legend.tex)



### L<sup>A</sup>T<sub>E</sub>X code

```
\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}
\addplot[draw=red, domain=0:360, ultra thick] {\sin(x)};
\addplot[draw=blue, domain=0:360, line width=1] {x/200};
\legend{\sin(x),\frac{1}{200}x}
\end{axis}
\end{tikzpicture}
\end{center}
```


## 25 pgfplots: Max and min for axes (xy-plane-axes-max-min.tex)



### L<sup>A</sup>T<sub>E</sub>X code

```
\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}[width=6in, height=2in, xmin=-100, xmax=500]
\addplot[draw=red, domain=0:360, ultra thick] {\sin(x)};
\addplot[draw=blue, domain=0:360, line width=1] {x/200};
\legend{\sin(x), \frac{1}{200}x}
\end{axis}
\end{tikzpicture}
\end{center}
```

## 26 pgfplots: Place Axes in Middle (xy-plane-place-axes.tex)



### L<sup>A</sup>T<sub>E</sub>X code


```

\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}[
width=6in, height=3in,
xmin=-100, xmax=500,
ymin=-1.5, ymax=3.5,
axis x line=middle,
axis y line=middle,
]
\addplot[draw=red, domain=0:360, ultra thick] {sin(x)};
\addplot[draw=blue, domain=-100:450, line width=1] {x/200};
\legend{$\sin(x)$,$\frac{1}{200}x$}
\end{axis}
\end{tikzpicture}
\end{center}


```

## 27 pgfplots: Points (pgfplots-points.tex)


Default style:



User-specified styles:



Points from functions:



L<sup>A</sup>T<sub>E</sub>X code

```
Default style:
\begin{center}
\begin{tikzpicture}
```

```
\begin{axis}[height=2in]
\addplot+[only marks] coordinates {(0, 2) (1, 2)};
\end{axis}
\end{tikzpicture}
\end{center}

User-specified styles:

\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in]

\addplot[mark=*,draw=red,fill=red,only marks] coordinates
{(0, 2) (1, 2)};

\addplot[mark=square*, draw=red, fill=red, only marks] coordinates
{(0, 1) (1, 1)};

\addplot[mark=square, draw=blue, fill=blue, only marks] coordinates
{(0, 0) (1, 0)};

\end{axis}
\end{tikzpicture}
\end{center}


Points from functions:
\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in]

\addplot[mark=*,draw=red,fill=red,only marks, domain=0:360] {sin(x)};

\end{axis}
\end{tikzpicture}
\end{center}
```

## 28 pgfplots: Insert PGF node (pgfplots-insert-node.tex)

The coordinate space of PGF is not the same as the coordinate space of pgfplots. To insert a PGF node into the right coordinates do the following.



### L<sup>A</sup>T<sub>E</sub>X code

The coordinate space of PGF is not the same as the coordinate space of pgfplots.



To insert a PGF node into the right coordinates do the following.

```
\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}
\addplot[draw=blue, domain=-200:360, line width=1] {x/200};

\node[]      at (axis cs:300,-0.5)    {$(300,-0.5)$};

\end{axis}
\end{tikzpicture}
\end{center}
```

## 29 pgfplots: Node with pin (pgfplots-pin.tex)



### L<sup>A</sup>T<sub>E</sub>X code

```
\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}
\addplot[draw=blue, domain=-200:360, line width=1] {x/200};
```

```
\node[pin=above left:{pin message on left}] at (axis cs:300,-0.5) {$(300,-0.5)$};

\end{axis}
\end{tikzpicture}
\end{center}


\begin{center}
\begin{tikzpicture}[line width=2]
\begin{axis}
  [width=6in, height=4in]

\addplot[draw=red, domain=-100:650, line width=1] {1000*x};
\addplot[draw=blue, domain=-100:650, line width=1] {x^2};
\addplot[draw=green, domain=-100:650, line width=1] {x^3/1000};

\node[pin=above left:{$y=1000x$}] at (axis cs:600,600000) {};
\node[pin=above left:{$y=x^2$}] at (axis cs:600,360000) {};
\node[pin=above left:{$y=\frac{1}{1000}x^3$}] at (axis cs:600,216000) {};

\end{axis}
\end{tikzpicture}
\end{center}
```

### 30 pgfplots: Pin Direction (pgfplots-pin-direction.tex)



#### L<sup>A</sup>T<sub>E</sub>X code


```

\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in, width=4in]
\addplot[draw=blue, domain=-100:100, line width=1] {x^2};
\node[pin=180:{$y=x^2$}] at (axis cs:100,10000) {};
\end{axis}
\end{tikzpicture}
\end{center}


\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in, width=4in]
\addplot[draw=blue, domain=-100:100, line width=1] {x^2};
\node[pin=225:{$y=x^2$}] at (axis cs:100,10000) {};
\end{axis}
\end{tikzpicture}
\end{center}

```


### 31 pgfplots: Shade Area (xy-plane-area.tex)



Same as above but with  $y$ -axis redrawn (i.e. complete cycle)



Area under curve specified with points:



#### LaTeX code

```

\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in,
stack plots=y,
area style,

```

```

enlarge y limits=false
]

\addplot [domain=0:360,
          blue,fill=red!90!black,
          line width=3pt
]
{sin(x)};

\end{axis}
\end{tikzpicture}
\end{center}

```

Same as above but with  $y$ --axis redrawn (i.e. complete cycle)

```

\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in,
stack plots=y,
area style,
enlarge y limits=false
]

\addplot [domain=0:360,
          blue,fill=red!90!black,
          line width=3pt
]
{sin(x)}
|- (axis cs:0,0) -- cycle;

\end{axis}
\end{tikzpicture}
\end{center}

```

Area under curve specified with points:



```

\begin{center}
\begin{tikzpicture}
\begin{axis}[height=2in,
smooth,
stack plots=y,
area style,

```

```
enlarge x limits=false
]
\addplot coordinates {(0,1) (1,1) (2,2) (3,2)} \closedcycle;
\addplot coordinates {(0,1) (1,1) (2,2) (3,2)} \closedcycle;
\addplot coordinates {(0,1) (1,1) (2,2) (3,2)} \closedcycle;
\end{axis}
\end{tikzpicture}
\end{center}
```

## 32 pgfplots: Steps (xy-plane-step.tex)



### L<sup>A</sup>T<sub>E</sub>X code

```

\begin{center}
\begin{tikzpicture}
\begin{axis}
\addplot+[const plot]
coordinates
{
(0,1) (1,3) (2,1) (4,6) (5,6) (6,2)
};
\end{axis}
\end{tikzpicture}
\end{center}

```

```
\begin{center}
\begin{tikzpicture}
\begin{axis}
\addplot[const plot]
coordinates
{
(0,1) (1,3) (2,1) (4,6) (5,6) (6,2)
};
\end{axis}
\end{tikzpicture}
\end{center}
```